

LED EMERGENCY LIGHTING

IP20 Surface Mount EM Escape Route 2.2W 130lm




3H

Emergency
Function

IES Data Files available

DIMENSIONS



All units are in mm

SPACING DATA

Mounting Height (m)	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape
2	10.9	9.9
2.5	12.9	10.9
3	13.9	12.9
3.5	15.9	14.9
4	17.9	16.9
6	24.9	19.6

KEY DATA

Power (Maintained)	4.9W
Luminous Flux	130lm
Colour Temperature	6500K
IP Rating	IP20
Dimensions	180 x 110 x 50mm
Warranty	3 Years

Part Number

NET-44-10-66

FEATURES & BENEFITS

- Battery and Gear all in one unit.
- Maintained or non-maintained Emergency.
- Compliant with EN 60598-2-22.

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.80
No. of LEDs	1
Driver Manufacturer	DPPUL
Total Circuit Power (W)	2.2 +/- 0.2W
Electrical Class	1
Operating Temp.	0°C to +40°C
Lamp Viewing Angle	70°
Lifespan _{L80}	50,000 Hours
Battery Pack	Ni-Cd C3.6V 3000 mAh
Battery Warranty	1 Year
Charge Time	24 Hours
Discharge Time	>3 Hours
Self Test	No
Maintained	No
Housing Material	Polycarbonate
Housing Colour	White
Weight	0.5Kg

SUITABLE FOR

- Indoor applications with surface mount option.
- Shaped beam angle for corridors and escape routes.