

## LED EMERGENCY LIGHTING

### IP65 EM Bulkhead 3W 150lm




ISO Legend kit included



Emergency Function

IES Data Files available

#### DIMENSIONS



#### TYPICALLY REPLACES

- 8W T5 Bulkhead.

All units are in mm

#### SPACING DATA

Mounting Height (m)	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape
2	11.4	9.4
2.5	12.8	10.2
3	13.7	10.9
3.5	14.5	11.4
4	15.1	11.4
6	16.2	11.1

#### KEY DATA

Power	3W
Luminous Flux	150lm
Colour Temperature	6500K
IP Rating	IP65
Dimensions	276 x 110 x 60mm
Warranty	3 Years

Part Number

NET-44-10-76

#### FEATURES & BENEFITS

- Includes ISO legend kit.
- Shatterproof all-polycarbonate housing.
- High lumens output.
- Rear or side entry.
- Maintained or non-maintained Emergency.
- Compliant with EN 60598-2-22.

#### TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.9
No. of LEDs	10
Driver Manufacturer	DPPUL
Total Circuit Power (W)	3W +/- 0.2W
Electrical Class	1
Operating Temp.	0°C to +40°C
Lamp Viewing Angle	60°
Lifespan <sub>L80</sub>	50,000 Hours
Battery Pack	Ni-Cd SC3.6V 1300 mAh
Battery Warranty	1 Year
Charge Time	24 Hours
Discharge Time	>3 Hours
Self Test	No
Maintained	Yes
Housing Material	Polycarbonate
Housing/Frame Colour	White
Weight	0.485Kg