

## LED TUBES

T8 Aluminium and Polycarbonate

2ft, 3ft, 4ft, 5ft, 6ft



### T8 600mm (2ft)

Power	10W
Luminous Flux	1050lm
Colour Temperature	5500K
IP Rating	IP20
Dimensions	604 x 28mm
Warranty	5 Years Extended

Part Number

NET-11-02-01

### T8 1200mm (4ft)

Power	18W
Luminous Flux	1900lm
Colour Temperature	5500K / 3000K
IP Rating	IP20
Dimensions	1213.6 x 28mm
Warranty	5 Years Extended

Part Number 5500K

NET-11-02-03

Part Number 3000K

NET-11-02-11

### T8 1800mm (6ft)

Power	32W
Luminous Flux	2900lm
Colour Temperature	5500K / 3000K
IP Rating	IP20
Dimensions	1778 x 28mm
Warranty	5 Years Extended

Part Number 5500K

NET-11-02-05

Part Number 3000K

NET-11-02-15

### T8 900mm (3ft)

Power	12W
Luminous Flux	1250lm
Colour Temperature	5500K
IP Rating	IP20
Dimensions	908.8 x 28mm
Warranty	5 Years Extended

Part Number

NET-11-02-02

### T8 1500mm (5ft)

Power	22W
Luminous Flux	2200lm
Colour Temperature	5500K / 3000K
IP Rating	IP20
Dimensions	1514.2 x 28mm
Warranty	5 Years Extended

Part Number 5500K

NET-11-02-04

Part Number 3000K


NET-11-02-13

### TECHNICAL SPECIFICATIONS (ALL MODELS)

Input Voltage AC	100-240V
Power Factor	>0.95
Luminous Efficacy	>100lm/W
LED Manufacturer	Honglitronic
LED Type	SMD 2835
Driver Manufacturer	Lifud
Driver Output Voltage DC	36-42V
Electrical Class	2
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan	50,000 Hours
Fire Rating	V-2
UGR Rating	22
End Cap Style	G13
Diffuser Material	Polycarbonate
Housing Material	Aluminium

IES Data Files available

### DIMENSIONS



Part Number	Dim A
NET-11-02-01	604.0
NET-11-02-02	908.8
NET-11-02-03 / 11	1213.6
NET-11-01-04 / 13	1514.2
NET-11-01-05 / 15	1778.0

All units are in mm

Rotatable end caps as standard

### COMPATIBLE ACCESSORIES

3H Tube EMKIT

NET-21-33-01

Page 236

DALI 3H Tube EMKIT

NET-19-33-17

Page 240