


LED PANEL LIGHTS

32W 600x600mm 3610lm




Tri-Colour



IES Data Files available

DIMENSIONS



All units are in mm

KEY DATA

Power	32W
Luminous Flux	3370lm / 3610lm / 3440lm
Colour Temperature	3000K / 4000K / 5500K
IP Rating	IP40
Dimensions	595 x 595 x 10mm
Warranty	5 Years Extended

Part Number

NET-11-03-12

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.95
LED Luminous Flux	4480lm
Luminous Efficacy	140lm/W
LED Manufacturer	Honglitronic
LED Type	SMD2835
No. of LEDs	240
Driver Manufacturer	Phillips
Driver Output DC	36-42V
Total Circuit Power (W)	32W +/-3W
Electrical Class	3
Colour Rendering	>80 CRI
Lamp Viewing Angle	115 °
Dimmable	Optional Upgrade
Flicker free	Yes
Operating Temp.	0°C to +50°C
Lifespan	50,000 Hours
UGR Rating	More than 19
Diffuser Flammability Rating	TP(a)
Diffuser/LGP Material	Polycarbonate/PMMA
Housing Material	Aluminium
Frame Colour	Silver
Weight	2.8Kg

TYPICALLY REPLACES

- 4 x 18W T8 fluorescent.
- 4 x 14W T5 fluorescent.
- 1 x 55W 2G11 fluorescent.

FEATURES & BENEFITS

- Selectable 3000,4000 or 5500K colour temperature via switch mechanism.
- Mounted driver for improved airflow.
- Compliant with EN 60598-2-2.
- High lumens per watt.
- Engineered back plate for rigidity.
- Multi layered wave path guide for even light distribution.

COMPATIBLE ACCESSORIES

40W Dimmable Driver	NET-42-43-16	Page 220
Suspension Kit	NET-46-16-02	Page 228
Surface Mount box	NET-11-03-39	Page 232
3H PNL EMKit	NET-21-33-03	Page 236
DALI EMKIT	NET-19-33-15	Page 240