


LED BATTENS

1800mm 80W (6ft)

Tri-Colour 3000K, 4000K and 5500K 10000lm




Tri-Colour



IES Data Files available

DIMENSIONS



All units are in mm



UK Emergency conversion
by Lux box Lighting Ltd

COMPATIBLE ACCESSORIES

Batten/NCF Suspension Kit	NET-46-16-04	Page 228
20mm Microwave Sensor	NET-42-43-20	Page 211

KEY DATA

Power	80W
Luminous Flux	9450lm / 10000lm/ 9830lm
Colour Temperature	3000K / 4000K / 5500K
IP Rating	IP20
Dimensions	1800 x 50 x 55mm
Warranty	5 Years Extended

Part Number	NET-11-11-10
Part Number EM	NET-11-11-99

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.9
LED Luminous Flux	10640lm
Luminous Efficacy	>133lm/W
LED Manufacturer	Honglitricon
LED Type	SMD 2835
No. of LEDs	338 x 2
Driver Manufacturer	Lifud
Driver Output Voltage DC	36-42V
Total Circuit Power (W)	80W +/-5W
Electrical Class	1
Emergency Operation*	>3H
Battery Pack*	LiFePO4
Emergency Conversion*	Luxbox
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Flicker free	No
Operating Temp.	-15°C to +45°C
Operating Temp. EM	0°C to +45°C
Lifespan	50,000 Hours
Fire Rating	V-0
UGR Rating	22
Diffuser Material	Polycarbonate
Housing Material	Aluminium
Housing Colour	White
Weight	1.58Kg

*Emergency version only

TYPICALLY REPLACES

- 2 x 70W T8 fluorescent.

FEATURES & BENEFITS

- Rear and end cable entry options.
- Simple clip design and interlocking power cord for easy installation.
- Flat end allows for end-to-end light designs.
- Compliant with EN 60598-2-1.