

LED SLIMLINE FLOOD LIGHTS

Motion and Photocell Sensor



Microwave
Motion Sensor



Photocell
Sensor

KEY DATA

Input Voltage AC	220-240V
Power Frequency	50/60Hz
Maximum Load	400W
Maximum Detection Distance	>6m
Detection Angle	150°
Operating Temp.	-15°C to +45°C
Duration	5 sec - 30 min
Lux Levels	2 - 100 lux or Disabled
IP Rating	IP65
Dimensions	70 x 63 x 35mm
Warranty	3 Years

Part Number

NET-42-04-39

FEATURES & BENEFITS

- Motion and Photocell functions can be used independently or simultaneously.
- Built-in override function.
- Suitable for Ramsey High Power and Heydon Slimline Flood Lights.
- Detection angle adjustable both vertically and horizontally.
- IP65 enclosure.

LED SLIMLINE FLOOD LIGHTS

Adjustable Wall Bracket



ADJUSTABLE WALL BRACKET ACCESSORY

Allows left to right orientation of a Flood Light with a maximum load of 3Kg.

Suitable for Heydon Slimline Flood Lights.

Part Number

NET-15-16-27

Product Summary

Part Number	Range	Description/Dimensions	Power	Colour Temp.	Lumens	Page
NET-15-04-32	Heydon	Slimline Flood Light	10W	6000K	990lm	170
NET-15-04-34	Heydon	Slimline Flood Light	30W	6000K	3350lm	171
NET-15-04-36	Heydon	Slimline Flood Light	50W	6000K	5590lm	172
NET-15-04-38	Heydon	Slimline Flood Light	80W	6000K	8640lm	173
NET-15-04-48	Heydon	Slimline Flood Light	100W	6000K	10860lm	174
NET-42-04-39	Heydon	Motion and Photocell Sensor	N/A	N/A	N/A	175
NET-15-16-27	Heydon	Slimline Flood Light Adjustable Wall Bracket	N/A	N/A	N/A	175