


LED NCF LUMINAIRES
1500mm 60W (5ft)
5500K 5330lm



IES Data Files available

DIMENSIONS



All units are in mm

COMPATIBLE ACCESSORIES

Batten/NCF Suspension Kit	NET-46-16-04	Page 228
20mm Microwave Sensor	NET-42-43-20	Page 211
Internal Microwave Sensor	NET-42-43-02	Page 210
Internal Daylight Switch	NET-42-43-10	Page 215
LED Non-Corrosive Emergency Kit	NET-21-33-09	Page 237
Tamper-proof clips	NET-11-16-23	Page 86

KEY DATA

Power	60W
Luminous Flux	5330lm
Colour Temperature	5500K
IP Rating	IP65
Dimensions	1560 x 130 x 85mm
Warranty	3 Years

Part Number

NET-11-11-25

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.9
LED Luminous Flux	5750lm
Luminous Efficacy	90lm/W
LED Manufacturer	Honglitronic
LED Type	SMD2835
No. of LEDs	324
Driver Manufacturer	Boke
Driver Output Voltage DC	27-40V
Total Circuit Power (W)	60W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	120°
Dimmable	No
Flicker free	No
Operating Temp.	-15°C to +45°C
Lifespan	35,000 Hours
Fire Rating	V-2
UGR Rating	More than 19
Diffuser Material	Polycarbonate
Housing Material	ABS
Housing Colour	Grey
Weight	2.6Kg

TYPICALLY REPLACES

- 2 x 58W T8 fluorescent.
- 2 x 35W T5 fluorescent.

FEATURES & BENEFITS

- Weather and dust-proof IP65 rated housing.
- Tamper-proof stainless steel retaining clips.
- Easy-mounting clips.
- Compliant with EN 60598-2-1.